

Non-reversing motor starter Size 1 3/4 Three phase full voltage Amb compensate bimetal OLrelay Contactor amp rating 40Amp 110-120/220-240VAC 60HZ coil Combination type 50Amp circuit breaker Encl NEMA type 4X 304 S-steel Water/dust tight noncorrosive Standard width enclosure



Figure similar

| General technical data                                       |                          |
|--------------------------------------------------------------|--------------------------|
| Weight [lb]                                                  | 35 lb                    |
| Height x Width x Depth [in]                                  | 24 × 11 × 8 in           |
| Protection against electrical shock                          | NA for enclosed products |
| Installation altitude [ft] at height above sea level maximum | 6560 ft                  |
| Ambient temperature [°F] during storage                      | -22 ... +149 °F          |
| Ambient temperature [°F] during operation                    | -4 ... +104 °F           |
| Ambient temperature during storage                           | -30 ... +65 °C           |
| Ambient temperature during operation                         | -20 ... +40 °C           |
| Country of origin                                            | USA                      |

| Horsepower ratings                                                         |       |
|----------------------------------------------------------------------------|-------|
| Yielded mechanical performance [hp] for three-phase AC motor               |       |
| <ul style="list-style-type: none"> <li>at 200/208 V rated value</li> </ul> | 10 hp |
| <ul style="list-style-type: none"> <li>at 220/230 V rated value</li> </ul> | 10 hp |
| <ul style="list-style-type: none"> <li>at 460/480 V rated value</li> </ul> | 0 hp  |

- at 575/600 V rated value

0 hp

### Contactors

|                                                                         |          |
|-------------------------------------------------------------------------|----------|
| Number of NO contacts for main contacts                                 | 3        |
| Operating voltage for main current circuit at AC at 60 Hz maximum       | 600 V    |
| Operating current at AC at 600 V rated value                            | 40 A     |
| Mechanical service life (switching cycles) of the main contacts typical | 10000000 |

### Auxiliary contact

|                                                                   |                                     |
|-------------------------------------------------------------------|-------------------------------------|
| Number of NC contacts at contactor for auxiliary contacts         | 0                                   |
| Number of NO contacts at contactor for auxiliary contacts         | 1                                   |
| Number of total auxiliary contacts maximum                        | 8                                   |
| Contact rating of auxiliary contacts of contactor according to UL | 10A@600VAC (A600), 5A@600VDC (P600) |

### Coil

|                                                                                |               |
|--------------------------------------------------------------------------------|---------------|
| Type of voltage of the control supply voltage                                  | AC            |
| Control supply voltage                                                         |               |
| <ul style="list-style-type: none"> <li>• at DC rated value</li> </ul>          | 0 ... 0 V     |
| <ul style="list-style-type: none"> <li>• at AC at 60 Hz rated value</li> </ul> | 110 ... 240 V |
| <ul style="list-style-type: none"> <li>• at AC at 50 Hz rated value</li> </ul> | 0 ... 0 V     |
| Holding power at AC minimum                                                    | 8.6 W         |
| Apparent pick-up power of magnet coil at AC                                    | 218 V·A       |
| Apparent holding power of magnet coil at AC                                    | 25 V·A        |
| Operating range factor control supply voltage rated value of magnet coil       | 0.85 ... 1.1  |
| Percental drop-out voltage of magnet coil related to the input voltage         | 50 %          |
| Switch-on delay time                                                           | 19 ... 29 ms  |
| Off-delay time                                                                 | 10 ... 24 ms  |

### Overload relay

|                                                                         |                      |
|-------------------------------------------------------------------------|----------------------|
| Product function                                                        |                      |
| <ul style="list-style-type: none"> <li>• Overload protection</li> </ul> | Yes                  |
| <ul style="list-style-type: none"> <li>• Test function</li> </ul>       | Yes                  |
| <ul style="list-style-type: none"> <li>• External reset</li> </ul>      | Yes                  |
| Reset function                                                          | Manual and automatic |
| Adjustment range of thermal overload trip unit                          | 0.85 ... 1.15        |
| Number of NC contacts of auxiliary contacts of overload relay           | 1                    |
| Number of NO contacts of auxiliary contacts of overload relay           | 0                    |

|                                                                                              |                                     |
|----------------------------------------------------------------------------------------------|-------------------------------------|
| Operating current of auxiliary contacts of overload relay                                    |                                     |
| <ul style="list-style-type: none"> <li>• at AC at 600 V</li> <li>• at DC at 250 V</li> </ul> | <p>10 A</p> <p>5 A</p>              |
| Contact rating of auxiliary contacts of overload relay according to UL                       | 10A@600VAC (A600), 5A@250VDC (P300) |

#### Enclosure

|                                                   |                                              |
|---------------------------------------------------|----------------------------------------------|
| Degree of protection NEMA rating of the enclosure | NEMA 4X 304 stainless steel enclosure        |
| Design of the housing                             | Dust-tight, watertight & corrosion resistant |

#### Motor Circuit Protector (magnetic trip only)

|                                                                           |               |
|---------------------------------------------------------------------------|---------------|
| Operating current of motor circuit breaker rated value                    | 50 A          |
| Adjustable pick-up value current of instantaneous short-circuit trip unit | 180 ... 600 A |

#### Mounting/wiring

|                                                                                                                             |                                                     |
|-----------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| (mounting position)                                                                                                         | Vertical                                            |
| (mounting type)                                                                                                             | Surface mounting and installation                   |
| Type of electrical connection for supply voltage line-side                                                                  | Box lug                                             |
| Type of connectable conductor cross-sections at line-side at AWG conductors single or multi-stranded                        | 1x (10 AWG ... 1/0 AWG)                             |
| Temperature of the conductor for supply maximum permissible                                                                 | 75 °C                                               |
| Material of the conductor for supply                                                                                        | AL or CU                                            |
| Type of electrical connection for load-side outgoing feeder                                                                 | Screw-type terminals                                |
| Tightening torque [lbf·in] for load-side outgoing feeder                                                                    | 35 ... 50 lbf·in                                    |
| Type of electrical connection of magnet coil                                                                                | Screw-type terminals                                |
| Tightening torque [lbf·in] at magnet coil                                                                                   | 5 ... 12 lbf·in                                     |
| Type of connectable conductor cross-sections of magnet coil at AWG conductors single or multi-stranded                      | 2x (16 ... 12 AWG)                                  |
| Temperature of the conductor at magnet coil maximum permissible                                                             | 75 °C                                               |
| Material of the conductor at magnet coil                                                                                    | CU                                                  |
| Type of electrical connection for auxiliary contacts                                                                        | Screw-type terminals                                |
| Tightening torque [lbf·in] at contactor for auxiliary contacts                                                              | 10 ... 15 lbf·in                                    |
| Type of connectable conductor cross-sections at contactor at AWG conductors for auxiliary contacts single or multi-stranded | 1x (12 AWG), 2x (16 ... 14 AWG), 2x (18 ... 16 AWG) |
| Temperature of the conductor at contactor for auxiliary contacts maximum permissible                                        | 75 °C                                               |

|                                                                                                                                  |                      |
|----------------------------------------------------------------------------------------------------------------------------------|----------------------|
| Material of the conductor at contactor for auxiliary contacts                                                                    | CU                   |
| Type of electrical connection at overload relay for auxiliary contacts                                                           | Screw-type terminals |
| Tightening torque [lbf·in] at overload relay for auxiliary contacts                                                              | 5 ... 12 lbf·in      |
| Type of connectable conductor cross-sections at overload relay at AWG conductors for auxiliary contacts single or multi-stranded | 2x (16 ... 12 AWG)   |
| Temperature of the conductor at overload relay for auxiliary contacts maximum permissible                                        | 75 °C                |
| Material of the conductor at overload relay for auxiliary contacts                                                               | CU                   |

### Short-circuit current rating

|                                                                                                      |                                              |
|------------------------------------------------------------------------------------------------------|----------------------------------------------|
| Design of the short-circuit trip                                                                     | Motor circuit protector (magnetic trip only) |
| Maximum short-circuit current breaking capacity (I <sub>cu</sub> )                                   |                                              |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 480 V</li> <li>• at 600 V</li> </ul> | <p>100 kA</p> <p>100 kA</p> <p>25 kA</p>     |

### Further information

**Industrial Controls - Product Overview (Catalogs, Brochures,...)**

[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:18EP92WGA81>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/US/en/ps/US2:18EP92WGA81>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:18EP92WGA81&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:18EP92WGA81&lang=en)

**Certificates/approvals**

<https://support.industry.siemens.com/cs/US/en/ps/US2:18EP92WGA81/certificate>





D68782001

last modified:

05/08/2019