

SIDOOR ATD430W control device for machine tools, up to 600 kg door weight, PROFINET IO CONFORMANCE Class C via 2x R45 sockets, EN 13849-1, EN953



Figure similar

General information	
Product type designation	ATD430W
Product version	With PROFINET interface
Optional product expansion	TRANSFORMER (6FB1112-0AT20-2TR0), TRANSFORMER UL (6FB1112-0AT21-2TR0), NT40 (6FB1112-0AT20-3PS0), DIN rail holder (6FB1144-0AT00-3AS0)
Manufacturer's article no. of the usable motor	6FB1103-0AT10-4MB0, 6FB1103-0AT10-3MC0, 6FB1103-0AT10-3MD0, 6FB1103-0AT11-4MB0, 6FB1103-0AT11-3MC0, 6FB1103-0AT11-3MD0, 6FB1103-0AT14-4MB1, 6FB1103-0AT13-4MB1, 6FB1103-0AT14-3MC2, 6FB1103-0AT13-3MC2, 6FB1103-0AT14-3MG2, 6FB1103-0AT13-3MG2
Manufacturer's article no. of the usable power supply unit	6FB1112-0AT20-2TR0, 6FB1112-0AT21-2TR0, 6FB1112-0AT20-3PS0, 6EP3446-8SB10-0AY0
Installation type/mounting	
Installation and mounting instructions	No direct solar radiation, final application-specific requirements must be observed. Installation outside a control cabinet only in horizontal mounting position
Supply voltage	

Design of the power supply	Via SIDOOR TRANSFORMER / SIDOOR TRANSFORMER UL / NT40 / SITOP PSU8200 13 A, 36 V or via DC
Rated value (DC)	36 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	38 V
Protection in case of DC supply	Use of a circuit breaker in the supply path according to 60898-1, 8A, C-characteristic type SIEMENS: 5SY4108-7 or 5SY4108-7KK11

Input current

I ² t, min.	30 A ² ·s
------------------------	----------------------

Encoder supply

Output voltage (DC)	24 V
short-circuit proof	Yes
Overload-proof	Yes
Remark	Ensure correct polarity! CAUTION: Do not supply with external voltage!

Output current

<ul style="list-style-type: none"> For output (24 V DC), max. 	400 mA
--	--------

Power

Active power input	145 W
Active power input, max.	540 W
Active power input (standby mode)	5 W

Digital inputs

Control inputs isolated	Yes
Control inputs p-switching	Yes

Input voltage

<ul style="list-style-type: none"> per DC input, min. 	10 V; Observe polarity !
<ul style="list-style-type: none"> per DC input, max. 	28 V; Observe polarity !

Input current

<ul style="list-style-type: none"> per DC input, min. 	9 mA
<ul style="list-style-type: none"> per DC input, max. 	27 mA

Digital outputs

Relay outputs

Switching capacity of contacts	
— at 30 V DC, min.	0.01 A
— at 30 V DC, max.	0.5 A

Mechanical data

Opening width of door, min.	0.3 m
Opening width of door, max.	5 m
Weight of door, max.	600 kg
Operating cycle frequency of door, max.	180 1/h

Counterforce, max.	75 N
Kinetic energy, max.	100 J

Interfaces

Interfaces/bus type	PROFINET IO according to Conformance Class C
---------------------	--

Isolation

Overvoltage category	2
----------------------	---

Degree and class of protection

IP degree of protection	IP20
-------------------------	------

Standards, approvals, certificates

Certificate of suitability according to EN 81	No
CE mark	Yes
UL approval	Yes
EAC (formerly Gost-R)	Yes
TÜV Inspectorate approval	Yes
PNO certificate	Yes
China RoHS compliance	Yes
Standard for EMC	EN 61000-6-2 / EN 61000-6-4
Standard for safety	EN 60950-1 / UL 61010-1 / UL 61010-2-201 / EN ISO 13849-1 Cat. 2 PL d

Ambient conditions

Ambient temperature during operation	
• min.	-20 °C
• max.	50 °C
• Remark	Screw control device thermally conductive onto a metallic mounting surface or standard rail mounting, otherwise the maximum operating temperature is only 40 °C

Ambient temperature during storage/transportation	
• Storage, min.	-40 °C
• Storage, max.	70 °C

Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m

Relative humidity	
• No condensation, min.	10 %
• No condensation, max.	93 %

Dimensions

Width	320 mm
Height	60 mm
Depth	80 mm

last modified: 07/11/2019