SIEMENS

| Data sheet | US2:HNF364PVPG |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manner of function of the actuating element | Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 600VDC A. Rating: 200A No. Of Poles: 3P F. Rating: 60Hz Action: SINGLE THROW Material: STEEL Enclosure: TYPE 1. 2-3 point mounting holes. O. Cycles: 8000 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: INDOOR SINGLE THROW |
| Mechanical service life (switching cycles) typical | 8000 |
| Mounting type | 2 OR 3 POINT MOUNTING HOLES |
| Number of poles | 3 |
| Electricity | |
| Ampacity | 200 A |
| Environmental conditions | |
| Ambient temperature during operation maximum | 49 °C |
| Ambient temperature during operation minimum | -29 °C |
| Model | |
| Product brand name | Siemens |
| Product type designation | ENCLOSED/SAFETY SWITCH |
| Mechanical Design | |
| Design of the housing | TYPE 1 |
| Material | STEEL |
| General product approval | |
| Certificate of suitability | UL |
| last modified: | 05/28/2019 |