GENERAL ACCESSORIES

Grounding Straps

Grounding straps can be used to provide electrical continuity between metal parts which must be electrically connected. Consists of braided copper with a ring terminal at both ends. Braid is insulated with green and yellow striped plastic.

Grounding Bars

Designed to provide a grounding area for controls and equipment. Has ten 10-32 tapped conductor holes and two mounting holes. Made of copper.

Door Stop Kit


For use on most SCE Type 4, 4X and 12 enclosures to lock door in the open position. Door opening must be at least 12 inches and must open horizontally. Designed to be installed at the bottom of the door opening. For installation information, consult our Installation Manual at www.saginawcontrol. com.

Provided with UL Recognized sealing washer to maintain Environmental Rating of the enclosure.


Removable Wire Cover

Designed to provide a "false" bottom in an enclosure with a bottom flange larger than 7 inches. Cover is bolted to a frame made of heavy gauge steel. Opens with a finger pull latch. A plate is provided to connect wire covers for a continuous bottom. Made of steel and powder coated white. For installation information, consult our Installation Manual at www. saginawcontrol.com.

Catalog	Approx. Wire	Length Between	Ring Terminal	Product	List
No.	Size (AWG)	Ring Terminals (CTOC)	Hole Size	Code	Price
SCE-GS808	#8	8.00	0.330	P2	




Catalog	Height	Width	Depth	Product	List
No.	(A)	(B)	(C)	Code	Price
SCE-GB10	1.00	4.00	0.25	P2	86.93



Catalog		Product	List	
No.	Finish	Code	Price	
SCE-DSTOPK	Zinc Plated	P2	67.05	



Catalog No.	Length (A)	Width (B)	Depth (C)	Enclosure Depth	Product Code	List Price
SCE-14RMW	6.00	35.00	14.00	18.00	P2	198.69
SCE-20RMW	6.00	35.00	20.00	24.00	P2	223.52



Phone (989) 799-6871 Fax (989) 799-4524

