

SIDOOR ATE500E CAN Control device for Elevator doors, horizontal, up to 280 kg door weight, 36VDC, 1*RS485, 1*CAN, 4*DI, 2*Relay 1*24VDC Out, -25-+50 °C



General information	
Product type designation	ATE500E CAN
Product version	With CAN interface
Optional product expansion	SIDOOR TRANSFORMER (6FB1112-0AT20-2TR0), SIDOOR TRANSFORMER UL (6FB1112-0AT21-2TR0), SIDOOR NT40 (6FB1112-0AT20-3PS0)
Manufacturer's article no. of the usable motor	6FB1203-0AT12-7DA0
Manufacturer's article no. of the usable power supply unit	6FB1112-0AT20-2TR0, 6FB1112-0AT21-2TR0, 6FB1112-0AT20-3PS0
Mean time between failures (MTBF)	19 y
Installation type/mounting	
Installation and mounting instructions	No direct solar radiation, final application-specific requirements must be observed. Installation outside a control cabinet only in horizontal mounting position NFPA elevator environment: Must be installed in a fire protection enclosure.
Supply voltage	
Design of the power supply	Via SIDOOR TRANSFORMER / NT40 or via DC
Rated value (DC)	36 V; with MED280: At 24 V DC max. door speed of 500 mm/s; at 28.8 V DC max. door speed of 800 mm/s

permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	38 V
Protection in case of DC supply	Use of a circuit breaker in the supply path according to 60898-1, 8A, C-characteristic type SIEMENS: 5SY4108-7 or 5SY4108-7KK11

Input current

I ² t, min.	30 A ² ·s
------------------------	----------------------

Encoder supply

Output voltage (DC)	24 V
short-circuit proof	Yes
Overload-proof	Yes
Remark	Ensure correct polarity! CAUTION: Do not supply with external voltage!

Output current

<ul style="list-style-type: none"> For output (24 V DC), max. 	400 mA
--	--------

Power

Active power input	85 W
Active power input, max.	540 W
Active power input (standby mode)	6 W

Digital inputs

Control inputs isolated	Yes
Control inputs p-switching	Yes

Input voltage

<ul style="list-style-type: none"> per DC input, min. 	10 V; Observe polarity !
<ul style="list-style-type: none"> per DC input, max. 	28 V; Observe polarity !

Input current

<ul style="list-style-type: none"> per DC input, min. 	3 mA
<ul style="list-style-type: none"> per DC input, max. 	15 mA

Digital outputs

Relay outputs

Switching capacity of contacts	
<ul style="list-style-type: none"> at 30 V DC, min. 	0.01 A
<ul style="list-style-type: none"> at 30 V DC, max. 	0.5 A

Mechanical data

Opening width of door, min.	0.3 m
Opening width of door, max.	5 m
Weight of door, max.	280 kg
Operating cycle frequency of door, max.	180 1/h
Kinetic energy, max.	75 J

Counterweight

<ul style="list-style-type: none"> with SIDOOR MED280 direct drive, max. 	6 kg
---	------

Interfaces	
Interfaces/bus type	CANopen, CiA standard 301, profile 417
Number of bus nodes	32
Isolation	
Overvoltage category	2
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
Certificate of suitability according to EN 81	Yes
CE mark	Yes
UL approval	Yes
EAC (formerly Gost-R)	Yes
TÜV Inspectorate approval	Yes
TÜV prototype tested	Yes
China RoHS compliance	Yes
Standard for EMC	EN 12015 / EN 12016 / EN 61000-6-2 / EN 61000-6-4 / EN 61326-3-1
Standard for safety	EN 60950-1 / EN 81-20 / UL 61010-1 / UL 61010-2-201 / EN ISO 13849-1 Cat. 2 PL d / IEC 62061: SIL 2
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C
• max.	50 °C
• Remark	Bolt the controller onto a metal mounting surface so that thermal conductivity is ensured
Ambient temperature during storage/transportation	
• Storage, min.	-40 °C
• Storage, max.	85 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
Relative humidity	
• No condensation, min.	10 %
• No condensation, max.	93 %
Dimensions	
Width	320 mm
Height	60 mm
Depth	80 mm
last modified:	07/11/2019