

## UBW

Frame Size	225	250	400	600	800	1200	2500
Rated Current - In 40° C	15,20,30,40,50,60,70,80,100,125,200,225	250	300,400	500,600	800	800,1200	1600,2000,2500
No.Of Poles	3	3	3	3	3	3	3
Rated operational Voltage-Ue	600	600	600	600	600	600	600
Max Options	2*	2**	2**	2**	2**	2**	3***
Reference standard	UL489	UL489	UL489	UL489	UL489	UL489	UL489

\*Factory Installed Only \*\* 1 Option-Right, 1 Option Left \*\*\* All Options Right Side Only

UL interrupting rating- Icu		N	H	L
Frame 225	120VAC	65kA	100kA	200kA
	240VAC	65kA	100kA	200kA
	480VAC	35kA	65kA	100kA
	600VAC	18kA	25kA	35kA
Frame 250	120VAC	65kA	100kA	200kA
	240VAC	65kA	100kA	200kA
	480VAC	35kA	65kA	100kA
	600VAC	18kA	25kA	35kA
Frame 400	120VAC	65kA	100kA	200kA
	240VAC	65kA	100kA	200kA
	480VAC	35kA	65kA	100kA
	600VAC	25kA	35kA	65kA
Frame 600	120VAC	65kA	100kA	200kA
	240VAC	65kA	100kA	200kA
	480VAC	35kA	65kA	100kA
	600VAC	25kA	35kA	50kA
Frame 800		<b>S</b>	<b>H</b>	
	120VAC	65kA	100kA	
	240VAC	65kA	100kA	
	480VAC	50kA	65kA	
	600VAC	25kA	35kA	
Frame 1200		<b>S</b>	<b>H</b>	<b>L</b>
	120VAC	85kA	100kA	200kA
	240VAC	85kA	100kA	200kA
	480VAC	50kA	65kA	100kA
	600VAC	25kA	35kA	45kA
Frame 2500		<b>N/A</b>	<b>H</b>	<b>L</b>
	120VAC	N/A	125kA	200kA
	240VAC	N/A	125kA	200kA
	480VAC	N/A	65kA	100kA
	600VAC	N/A	50kA	65kA

Options available for all

Frame Sizes:
Auxiliary Contacts*
Alarm Contacts*
Shunt Trip Units *
Undervoltage Trip Units*

\* 225 Frame must be Factory Installed